

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence, note discrepancies in the record, state method of establishing or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography, ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 2 HES 578 T. 31 N R. 32 W P.M.M. Lincoln County

ORIGINAL G.L.O. NOTES: 1916

CORNER: Slate stone 36 x 10 x 7 inches, 26" in the ground, marked 2 HES 578 on SE face and + on top
 13" Fir bears S.62°35'E., 44 lks
 9" Fir bears S.11°45'E. 44 lks
 Mound of stones, 4 ft. base, 2 ft. high, SE of corner

EVIDENCE FOUND: Slate stone 10 x 10 x 7 inches, marked 2 HES 578 on SE face and + on top
 Mound of stones, 4 ft. base, .5' high, SE of corner
 No evidence of BT's



mkd orig stone



mound of stones

SKETCH OF CORNER

CERTIFICATION

I, _____
 certify the information shown herein is true and correct.

Signature of _____

I, Robert S. Custer
 certify that this Corner Record correctly represents work performed
 by me or under my direction in accordance with the Corner
 Recordation Act (70-22-31) M.S.

Signature of _____

Date: 11/30/81

Reg. No. 33258


Employer: Professional Consultants, Inc.

Office of Clerk and Recorder, County of Lincoln. This "corner
 record" was filed for record on the January 31st day of 1982
 was noted on the cross-index plat and is assigned page No. 1501, in
 book No. 1

Eleanor L. Vaughn by Betty L. Conces
 County Official deputy

Cross Index No. L-12,13 T. 31N R. 32W P.M.M.

Sec. 16 - Unsurveyed



• - corner this sheet