

## CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found original corner monument loosely set with brass cap marked (Record - set an iron post, 3 ft. long, l in. in diam.,  $2^{l}$  in. in the ground) from which: A 22 in. Ponderosa Pine bears S.  $80^{10}_{2}$  W. -  $^{l}$ 46 lks - with scribing visible  $^{l}$ 4 S. 25 BT (Record - a 20 in. black pine, bears S.  $80^{10}_{2}$  W.,  $^{l}$ 46 lks dist. marked  $^{l}$ 4 S. 25 BT.)

1 S 24 4 S 25

1916

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Reset original corner monument from record bearing and distance from the one original BT. Reset the iron post 3 ft. long, 1 in. in diam., 26 in. in ground with brass cap marked and raised a collar of stone and earth 2 ft. base, 1 ft. high around the iron post, from which:

1 S 24

Date of work: 4/10/70

1916

• = Corner recorded on the sheet

A 9 in. Douglas Fir bears, N.  $54^{\circ}$  E. - 16 lks - mkd rm

A 12 in. Douglas Fir bears, S. 66° E. - 25 lks - mkd rm

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original G.L.O: notes)

Surveyor's Seal	A. R. TRENKLE	DIAGRAM OF CORNER:
	certify that the information shown herein is true and	N. T31N R32W
	a. R. Triendle	1 S 24 5 25
	Signature of Ground Party Chief	* S 25
	STANLEY J. SKOUSEN	1
	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same	

Stanley | Skyuse Signature of Surveyor

> 2532 S Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 27th. day of April 19.70, was noted on the cross-index plat and is assigned page No. 179 in book No. 1

ELEANOR L. VAUGHN, By County Official Deputy

Cross Index No. R-23 T 31 R 32 Mer.