

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found original corner monument firmly set with brass cap marked (Record set an iron post 3 ft. long, 2 in. in diam. 24 in. in the ground with brass cap marked) from which: A 12 in. Fir stump bears S. $62\frac{1}{2}^{\circ}$ W. - 102 lks with lower edge of blaze visible. (Record a 9 in. Fir bears S. 62° 36' W. - 102 lks mkd with an X and 5 HES 935 BT.) The other BT was destroyed by a road.

5
HES
935
1916

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 4/10/70

I raised a collar of stone 3 ft. base $1\frac{1}{2}$ ft. high around the iron post with brass cap marked, from which:

A 13 in. Ponderosa Pine bears S. $66\frac{1}{2}^{\circ}$ E. - 7 lks - mkd rm

A 12 in. Larch bears N. $32\frac{1}{2}^{\circ}$ W. - 15 lks - mkd rm

5
HES
935
1916

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original field notes)

Surveyor's Seal

I, A. R. TRENKLE
certify that the information shown herein is true and correct.

A. R. Trenkle

Signature of Ground Party Chief

I, STANLEY J. SKOUSEN
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Stanley J. Skousen
Signature of Surveyor

DIAGRAM OF CORNER:
T31N R32W

N.
5
HES
935

* = Corner recorded on the sheet

2532 S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 27th. day of April 1970, was noted on the cross-index plat and is

assigned page No. 181, in book No. 1

ELEANOR L. VAUGHN, By: *Mae Watson*
County Official Deputy

Cross Index No. L-M-19 T. 31 R. 32 Mer.