

CERTIFIED LAND CORNER RECORDATION  
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)


Found original stone firmly set and plainly marked (Record - set a small stone, marked with a cross (X) under a sandstone 24 X 12 X 10 inches marked 7 HES 440 on S. face with a cross (X) on top for exact corner point.) from which: A 15 in. Fir bears N 1° E. - 27 lks - stump with blaze, (Record - a cross (X) on a Douglas Fir tree 12 in. diam. bears N. 1° 00' E. - 27 lks dist.) A 14 in. Fir bears S. 84° E. - 12 lks - stump and burned, (Record - a cross (X) on a Douglas Fir tree 12 in. diam. bears S. 84° 00' E. - 12 lks dist.; each blazed and scribed 7 HES 440 BT.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED  
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

I set a 2 in. galvanized iron pipe 20 inches in ground, with brass cap marked, and raised a collar of stone, 3 ft. base 1 ft. high around the iron pipe. I set the iron pipe in the exact position of the original stone corner monument and buried the original stone alongside the iron pipe, from which:

- A 7 in. Douglas Fir bears S. 31½° E. - 46 lks - mkd rm
- A 8 in. Douglas Fir bears N. 50½° W. - 86 lks - mkd rm

Date of work: 4/13/70



SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.  
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)


(Record from original field notes)

Surveyor's Seal

I, A. R. TRENKLE  
certify that the information shown herein is true and correct.  
A. R. Trenkle  
Signature of Ground Party Chief

I, STANLEY J. SKOUSEN  
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.  
Stanley J. Skousen  
Signature of Surveyor

DIAGRAM OF CORNER:



o = Corner recorded on the sheet

2532 S  
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 27th day of April 1970, was noted on the cross-index plat and is

assigned page No. 182, in book No. 1

ELEANOR L. VAUGHN, By: Mae Watson  
County Official Deputy.

Cross Index No. 0-23 T. 31 R. 32 Mer.