

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found original stone firmly set and plainly marked (Record - set a quartzite stone 26 X 10 X 10 ins. 16 ins. in the ground, with a cross (X) on top, marked 5 HES 751 on SE face., marked 4 HES 744 on NW face.) from which:
A cross (X) on a fir tree 15 in. diam. bears N 4°50'W - 84 lks. Dist., alive and overgrown. (Record - A cross (X) on a fir tree 5 in. diam. bears N 4°50'W - 84 lks. dist., blazed and scribed 4 HES 744 BT.)
A fir 16 in. diam. bears S 71° 23'E - 9.5 lks. dist., stump with scribing visible. (Record - A cross (X) on a fir tree 15 ins. in diam. bears S 71° 23'E - 9.5 lks. Dist. blazed and scribed 5 HES 751 BT.)
A lodgepole pine 12 in. diam. bears S 4° 22'W - 87.5 lks. dist., stump with scribing visible. (Record - A cross (X) on a lodgepole pine tree 8 ins. in diam. bears S 4° 22'W, 87.5 lks. Dist., blazed and scribed 5 HES 751 BT.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 10/29/70

Corner common to cors. 4 HES 744 and 5 HES 751.
I set a 2 in. galvanized iron pipe 24 inches in the ground, with brass cap marked. I buried the original corner stone alongside the iron pipe, from which:

SJS 2532 S
HES
744
4
5
HES
751
1970

A larch 8 ins. diam. bears N 61°E - 18 lks. dist., marked RM.
I placed signs and paint on BT's and placed an iron fence post alongside the iron pipe with signs attached.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original field notes.)

Surveyor's Seal

I, A. R. Trenkle
certify that the information shown herein is true and correct.


A. R. Trenkle
Signature of Ground Party Chief

I, Stanley J. Skousen
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Stanley J. Skousen
Signature of Surveyor

DIAGRAM OF CORNER:

N. T 31N.R32W



= Corner recorded on the sheet

2532 - S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 20th. day of April 1971, was noted on the cross-index plat and is assigned page No. 214, in book No. 1

ELEANOR L. VAUGHN, By: Mae Watson
County Official Deputy

Cross Index No. M-24 T. 31 R. 32 Mer.