Original and/or subset record used to evaluate the corner position.
Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

Description of monument and accessories set to perpetuate the corner position.
Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

T. 31N R.32W & 33W P.M.M. Lincoln Corner <u>Sec's 12, 7, 13, 18</u> _ County

ORIGINAL G.L.O. NOTES: 7,12,13 & 18 T31N, R32 & 33W, 1893

CORNER: Set 4' long 4" sq. post 24" in ground marked T31N, S7 on N.E.; R32W, S18 on SE

A Fir 12" dia bears N.41 1/4°E., 20 1ks distance marked T31NR32W S7 BT A Fir 10" dia bears S.43 1/2°E., 46 lks distance marked T31NR32W S18 BT A Fir 6" dia bears S.41°W., 20 1ks distance marked T31NR33W S13 BT A Fir 8" dia bears N.18°W., 42 lks distance marked T31NR33W S12 BT

EVIDENCE FOUND: A rotten fir stump with scribed face bears N.41°E., 13.2 feet

A 14" Fir with well healed blaze bears S.44°E., 30.4 feet A 16" Fir with well healed blaze bears S.41°W., 13.2 feet

A rotten fir stump 10" dia with scribed face bears N.18°W., 27.7 feet

Set 2 1/2" brass cap in mound of stone at record distance - distance intersect from found original BT's

New RM's 12" dia Fir bears N.22°E., 32.0 feet marked RM with BT tag 12" dia Fir bears S.84°W., 24.4 feet marked RM with BT tag

Z'/2" Brass cap in mound stona

SKETCH OF CORNER

CERTIFICATION certify the information show shown herein is true a Robert Employer: Professional Lonsultants, Inc.

Sec. 13 Office of Clerk and Recorder, County of Lincoln ___ . This ''corner January 215t ___ day of 1982 record" was filed for record on the _ Eleanor L. Vaughn book No. 🚣 County Official

Cross Index No. J-25 T. 31N R. 33W PMM

· - corner this sheet