INSTRUCTIONS

- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- Description of evidence rooms, incomposition.
 Description of monument and accessories set to perpetuate the corner position.
 Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
 Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
 Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

T. ______R. _____P.M.M. NW 1/16 of Sec. 4. Corner_ County

- No original record.
- II. No original record.
- III. At the position determined by survey, set a 2 1/2 in. diam., 30 in. long aluminum pipe, 26 ins. in the ground, with a 3 1/4 in. U.S.D.A. Forest Service aluminum cap marked as shown:



Established two bearing trees:

A fir, 10 ins. diam., bears N27 $^{\circ}$ E, 22.8 ft dist., scribed NW 1/16 S 4 BT. A fir, 15 ins. diam., bears S82 $^{\circ}$ E, 17.2 ft dist., scribed NW 1/16 S 4 BT.


Painted a red band around bearing trees and attached Land Survey Monument and Bearing Tree signs.

Set a 6 ft. galvanized steel post with Land Survey Marker and Property Boundary decals, NORTH, 3 ft.

Magnetic Declination: 20 East.

A Production of the second of	N	CERTIFICATION Rex O. Rice certify the information shown herein is true and correct. Signature Ground Party Chief Alvah F. Hughes certify that this Corner Record correctly represents work p by me or under my direction in compliance with the
SETCH OF CORNER		Recordation Act. (70-22-10), et seq. M.C.A.). Signature of Surveyor & Seal Date: 12/21/93 Reg. No. 7322LS Employer: U.S. POREST SURVICE
an again in a sala Lang.	\mathcal{Q}	Sec. 4

Office of Clerk and Recorder, County	of Allis "co	rner
record" was filed for record on	Jan 12, 1994	<u>.</u>
was noted on the cross-index plat and	l is assigned page No6072	_ , in
book No.	Caral M. Cumming &	DB
	. Cross Index No T 7 8 R 8	W PMN



· - corner this sheet