CERTIFIED CORNER RECORDATION

Corner W.C. W1/4 Sec. 22 T. 31N R. 34W P.M., MT Lincoln County

I. 1903 G.L.O. Original Survey record by Allen B. Benedict: Point for witness cor. to 1/4 sec. cor. falls on a boulder in place, 10x8 ft. above ground, cut a cross (x) at the exact point for witness cor. to 1/4 sec. cor., mkd. "W.C. 1/4" on the W. side.

from which:


A fir, 5 ins. diam., bears N19°30'E, 30 lks. dist., mkd. "WC 1/4 S22 BT". A pine, 24 ins. diam., bears S55°W, 14 lks. dist., mkd. "WC 1/4 S21 BT".

II. The rock outcrop has eroded over time, causing original marks to become lost.

from which:

A pine, 25 ins. diam., bears N55°E, 9.24 ft. dist., mkd. "WC 1/4 S22". (1903-record-S55°W-WC 1/4 S21)

III. I remonument this corner by record distanc and bearing from the found original bearing trees. Set a 30 in. driveable aluminum rod, 20 ins. in the ground, with a 3 1/4 ins. diam. aluminum cap mkd. as shown below.



Established one bearing tree and set one galvanized witness post:

A pine, 11 ins. diam., bears S64°W, 44.3 ft. dist., mkd. "WC 1/4 S21 BT".

A 6 ft. steel guard post, North, 4.0 ft. dist. of the cor. with a Land Survey Monument decal.

Painted red bands around the bearing tree and attached Land Survey Monument and Bearing Tree signs. Attached a location poster on an 8 in. diam. cottonwood, on the S. side of the Snowshoe Mine Rd.

CERTIFICATION

Magnetic Declination: 20° East.

