
CERTIFIED CORNER RECORDATION

Corner	S 1/16	Secs.	17 & 18	Т.	31N	R.	34W	P.M., MT	Lincoln	County

I. <u>1982 Certified Corner Recordation by Jack H. Ninneman, 4661S</u>: This corner was not previously set. Set a 3" x 30" aluminum capped monument marked as shown below.



from which:

A 14" Larch, bears \$70°E, 11.9 feet, scribed "\$1/16 \$17 BT" and posted.

A 10" Larch, bears S85°W, 18.0 feet, scribed "S1/16 S18 BT" and posted.

A location poster on a 10" Cedar, bears N27°W, 5.0 feet.

Painted monuments and accessories with bright red paint.

II. Found a 3 in. diam. aluminum capped monument, protruding 5 ins. above the ground, mkd. as shown and witnessed by the original bearing trees and location tree.

from which:

A larch, 16 ins. diam., bears S70°E, 11.9 ft. dist., with a healed face.

A larch stump, 10 ins. diam., bears S85°W, 18.0 ft. dist., with visible scribe.

A location poster on a 14 in. diam. cedar, bearing N27°W, 5.0 ft. dist. of the monument.

A carsonite post, with a Property Boundary decal attached.

III. Used the existing location tree, for the new bearing tree:

A cedar, 14 ins. diam., bearing N27°W, 5.0 ft. dist., mkd. "S 1/16 S18 BT".

Painted red bands around the bearing tree and attached Land Survey Monument and Bearing Tree signs.

Magnetic Declination: 20° East.

