

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

### CERTIFIED CORNER RECORDATION

Corner: Section Corner, Secs 4, 5, 32 & 33 T. 31 & 32N. R. 34W. P.M.M. Lincoln County

GLO Record: Set limestone and established 4 bearing trees.

1982 Record: Found original stone.  
 (Staab 5619S) Stump hole, bears N8°15'E, 51 lks (33.7 ft.)  
 Larch, 20 ins. dia., bears S55°E, 77 lks (50.8 ft.), w/ overgrown scribe  
 Pine, 12 ins. dia., bears S50°W, 39 lks 25.7 ft.), w/ overgrown scribe  
 Leaning snag, 50 ft. high, bears N29°30'W, 69 lks (45.5 ft.), w/ visible scribe

Set a 32 ins. x 3-1/2 ins. dia. alum. pipe, 25 ins. in the ground w/ alum. cap. Buried the original stone alongside. Raised a 3 ft. dia. collar of stone around monument.

From which:

- Fir, 6 ins. dia., bears N41°E, 35 lks (23.1 ft.), marked "T32N R34W S33 BT"
- Fir, 6 ins. dia., bears N45°W, 26 lks (17.2 ft.), marked "T32N R34W S32 BT"

2010 Found: We find a 3-1/4 ins. dia. alum cap, marked as shown below, on 2-1/2" dia. pipe, rising 0.3 ft. from a mound of stone. From which:

- Grand Fir snag, 10 ins. dia., bears N43°30'E, 22.5 ft., w/ overgrown blaze & BT tag
- Larch snag, 20 ins. dia., bears S54°30'E, 52.1 ft., w/ overgrown blaze & tag
- Grand Fir snag, 10 ins. dia., bears S51°W, 25.2 ft., w/ overgrown blaze
- Douglas Fir snag, 20 ins. dia., bears N29°W, 46.1 ft., Scribed "32 R 34 S32"

2010 Perpetuation: We establish new reference monuments as follows:

- Hemlock, 13 ins. dia., bears N11°E, 40.0 ft., scribed "T32N R34W S33 BT"
- Hemlock, 8 ins. dia., bears S39°30'E, 13.4 ft., scribed "T31N R34W S4 BT"
- Grand Fir, 7 ins. dia., bears S72°W, 12.8 ft., scribed "T31N R34W S5 BT"
- Douglas Fir, 12 ins. dia., bears N66°W, 9.1 ft., scribed "T32N R34W S32 BT"

We set galvanized steel posts, West, 1.8 ft. and East, 2.2 ft. from the monument w/ LSM and USFS boundary decals.

Bearing trees were affixed with BT tags, snow blazed and a painted red band.

**SKETCH OF CORNER**

**CERTIFICATION**

I, Keith Brandt  
 certify the information shown herein is true and correct.  
*Keith Brandt*  
 Signature Ground Party Chief

---

I, Ken E Jenkins  
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22101, et seq.).  
*Ken E Jenkins*  
 Signature of Surveyor & Seal REGISTERED

Date: 10/2010 Reg. No. 9330 LS  
 Employer: Montana Northwest Company  
PO Box 8777, Missoula, MT 59807  
406-721-4033 Project No. 1617-10

Office of Clerk and Recorder, County of \_\_\_\_\_ This "corner  
 record" was filed for record o 231790 BOOK: CCR CC&R'S PAGE: 11759 Pages: 1  
 STATE OF MONTANA LINCOLN COUNTY  
 was noted on the cross-index RECORDED: 03/30/2011 11:10 KOI: CC&R'S  
 book No. \_\_\_\_\_ TAMMY D. LAUER CLERK AND RECORDER  
 FEE: \$0.00 BY: *Deanna Deussen Deputy*  
 TO: MONTANA NORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA

County Official

Sec. 4

