

## INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner S $\frac{1}{4}$  Corner Sec. 14 T. 31N R. 34W P.M.M. Lincoln County

1.

40.10 chains: Set a granite stone, 12 X 10 X 8 inches, 8 inches in the ground, for  $\frac{1}{4}$  sec. corner, marked  $\frac{1}{4}$  on N. face, from which,

A Pine, 8 inches diameter, bears S.  $4^{\circ}$  E, 60 links distance, marked  $\frac{1}{4}$ S23B.T.

A Pine, 6 inches diameter, bears N  $45^{\circ}30'$  W., 5 links distance, marked  $\frac{1}{4}$ S14B.T.


2.

Found: B.L.M. brass capped monument marked as shown below from which,

A 9" Pine bears S12 $\frac{1}{2}^{\circ}$ E 32 links 21.12 feet. Scribing overgrown. Posted  
A location poster on an 18" Fir which bears N  $42^{\circ}$  W 2.6 feet.

Scribing overgrown. Posted.

Painted monument and accessories with bright red paint.



Found B.L.M. brass capped monument marked as shown.

A LOCATION POSTER  
ON AN 18" FIR WHICH  
BEARS N  $42^{\circ}$  W 2.6  
FT.



N  $42^{\circ}$  W  
2.6 FT.

S12 $\frac{1}{2}^{\circ}$  E  
32  
21.12 FT.

9" PINE  
BT

SKETCH OF CORNER

## CERTIFICATION

I, Bill Bahme

certify the information shown herein is true and correct.

Bill Bahme

Signature Ground Party Chief

I, Jack H. Ninneman

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

Jack H. Ninneman

Signature of Surveyor & Seal

Date: Aug. '82 Reg. No. 4661S


Employer: Ninneman Engineering Inc.

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the Oct. 20 day of 1982 was noted on the cross-index plat and is assigned page No. 1976, in book No. \_\_\_\_\_

Eleanor L. Vaughn by Betty L. Conces  
County Official deputy

Cross Index No. N-19 T. 31N R. 34W P.M.M.

Sec. 14



• corner this sheet