

CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the S. corner common to sections 5, 6, 7, & 8, T33N, R26W, MPM, Lincoln County, Montana, we find; A piece of 4" X 4" tamarack about one foot long, clearly scribed, lying loose on the ground near a small group of rocks (Record: A tamarack post, 3 ft. long, 4" sq., 24" in the ground, - - - -) from which: Two 10" LPP clearly scribed for S. 5 & 8 lying loose on the ground bearing S 57° E approx. 50 links away in a dozer pile (Record: bears N 49° E, 26 links dist., marked T33N R26W S 5 BT) (Record: bears S 32½° E, 29 links dist., marked T33N R26W S 8 BT). A slab of a pine tree clearly scribed T33N R26W S 6 BT was found lying loose at edge of dozer pile about 30 links due east of where section of scribed post was found (Record: a pine 10" dia. bears N 85½° W, 13 links dist., marked T33N R26W S 6 BT). An attempt was made to locate the bearing tree in section 7 but when the record was checked the BT would be in a main road and no evidence was found (Record: A pine 12" diameter bears S 68½° W, 35 links dist., marked T33N R26W S 7 BT).

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

We position the corner under the original wood stake, which was Date of work: 5/23/66 not in its original position, but placed there to mark the position of the corner by chaining in from the quarter corners north, south, east, and west. This position falls along the original blaze line north, west, and east of the corner. The blaze line is eradicated immediately south of the corner. In addition, one member of the party, John Aemisegger, in 1944 placed a location poster on a line blazed tree marked 1 chain east of corner. The position chosen falls about 125 links west of his location poster. At the point chosen we set a 30" galv. pipe, 20" in the ground with a brass cap on it scribed as follows: T33N R26W

6 5
1966 858ES

I. M. Tillotson

packed tightly with rock underground and ringed with a mound of rock on the surface.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

We create two new reference monument trees which bear from the corner as follows: A 14" larch bears N 2° W, 61 links and a 20" larch bears N 80° E, 36 links dist., both double blazed and scribed "RM". We posted BT, property and location signs.

orig. 17d 11g

Note: This corner was dozed out. It was set after a fire ran through the area. The LPP bearing tree died immediately after blazing. We skimmed off the dozer fill in a circle 8 feet dia. looking for original wood stake hole without success.

Surveyor's Seal

Ira M. Tillotson, J. L. Aemisegger,
We / J. W. Coleman, A. W. Cannon
certify that the information shown herein is true and correct.


Signature of Ground Party Chief

I, Ira M. Tillotson
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Ira M. Tillotson + = Corner recorded on the sheet
Signature of Surveyor

858ES
Registration Number

DIAGRAM OF CORNER:



Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 12th day of April 1968, was noted on the cross-index plat and is assigned page No. 101, in book No. 1

Eleanor L. Vaughn
County Official
Cross Index No. E-5 T. 33N R. 26W Mer.