CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the $\frac{1}{4}$ corner common to S. 16 & 21, T33N, R26W, P.M.M., Lincoln Co., Mont., we find; A granite stone, 6" X 8", X 4" above ground, marked " $\frac{1}{4}$ " on north face, set firmly, (Record: Granite stone, 14 X 12 X 10 ins., --) from which: A 8" LPP, scribing plain, bears N 2° E, 28 links (Rec.: 4" pine bears N $\frac{1}{2}$ ° E, 28 links) & a fallen dead 6" LPP, the root crown hole of which bears S 28° E, 18 links (Rec.: 4" pine bears S $\frac{1}{2}$ ° E, 18 links).

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

To perpetuate this corner we pile a large ring of rocks around the original corner stone and create two new reference monument trees which bear from the corner as follows: A 5" larch bears S 18° E, 56 links dist. & a 4" larch bears N 50° W, 31 links dist., both double blazed and scribed "RM". We posted boundary, location, attention and bearing tree signs. We posted bearing tags on each new RM.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal

Ira M. Tillotson, J. L. Aemisegger, We Y J. W. Coleman, A. W. Cannon certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, Ira M. Tillotson certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

of Surveyor

DIAGRAM OF CORNER:

516 <u>1</u> 521

= Corner recorded on the sheet

858 E S Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 2th day of April 1968, was noted on the cross-index plat and is assigned page No. 103, in book No. 100 County Official Mac Watson, Let.