

CERTIFIED CORNER RECORDATION

CORNER C 1/4 S 24 T. 33 N., R. 26 W., P.M.M. LINCOLN COUNTY

RECORD:
NONE

FOUND EVIDENCE:
NONE

PERPETUATION:

Set a 3 1/4 inch aluminum cap stamped (see diagram below) on a 5/8 inch dia. rebar 30 inches long.
From which

A 7 1/2 inch DBH Spruce scribed T33N R26W C 1/4 S24 BT bears N 8° W 3.8 ft. dist.


A 6 1/2 inch DBH Spruce scribed C 1/4 S24 BT bears S 17° W 7.1 ft. dist.

Painted 6 inch wide bands and attached bearing tree signs to trees.

MAGNETIC DECLINATION: 18° E

7.5" Spruce

N 8° W
3.8'



S 17° W
7.1'

6.5" Spruce

CERTIFICATION

I, GEORGE CLARK

Certify the information shown herein is true and correct

Signature of Ground Party Chief

I, KENNETH E. DAVIS

that this Corner Record correctly represents work
performed by me or under my direction in compliance with the
"Montana Corner Record Act"

10-21-2005 (1 sec, M.C.A.)

1975-S

Surveyor & Seal

See: 607442 Reg. No. 4975-S

Employment DAVIS Surveying INC

SKETCH OF CORNER

SECTION

Office of Clerk and Recorder, County of _____

This "corner record" was filed for record on

was noted on 189392 BOOK: CCR CC&R'S PAGE: 10867 Pages: 1

No. _____ STATE OF MONTANA LINCOLN COUNTY

In book No. _____ RECORDED: 11/04/2005 12:54 KOI: CC&R'S

CORAL M. CUMMINGS CLERK AND RECORDER


FEE: \$0.00

BY: [Signature]

TO: DAVIS SURVEYING, INC.

Cross Index No. C 1/4 S 24 T. 33 N., R. 26 W., P.M.M.

THIS CORNER



Sec
24