

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner N¹/₁₆ Between Sections 29 & 28 T. 33N R. 26W P.M.M. Lincoln County

Original & Subsequent Records: None prior to this survey.

Corner set by single proportion: See C of S No. 1003

Set standard 2" diameter aluminum monument with 3" cap stamped as shown below. From the monument:

A 11" pine scribed "N¹/₁₆ S 29 BT" bears S 54° W 3.8'

A 10" pine scribed "N¹/₁₆ S 28 BT" bears S 72° E 7.6'



SKETCH OF CORNER

CERTIFICATION

I, Thomas Van Slyke,
certify the information shown herein is true and correct.

Thomas Van Slyke
Signature Ground Party Chief

I, S. R. Smith,
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

S R Smith
Signature of Surveyor & Seal


Date: 11/13/82 Reg. No. 47405

Employer: Smith Surveying Co.

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the March 2nd day of 1982 was noted on the cross-index plat and is assigned page No. 1554, in book No. 1

Cross Index No. S-9 T. 33N R. 26W P.M.M.

Sec. 29



• - corner this sheet