## INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.

  Description of evidence found, note discrepancies in the record, state method of establishing
- Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- Certification must be signed and sealed by Registered Land Surveyor in State of Montana. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

1/4 Corner Common To Sections 29 & 30 T. 33N R. 26W P.M.M. Lincoln 610 Record: Set a slate stone, 15 x10 x8 ins. 10 ins. IN the ground, mkd. "1/4" or West face, from which:

A 36" Tamarack mkd. "1/4 S29 BT" bears N531/2 E 371ks.

A 4" Fir mkd. "/4 S 30 BT" bears S 73/2°W 17 1ks.


BIM Record: Found stone as described by GLO, from which: A 36" Larch Stump mkd. "/4 529 87" bears NS3/2 = 371ks. A 12° fir with overgrown face bears 571/2°W 17 1ks. At the corner point, set an iron post, 30"long, 21/2" diam., 26" in the ground, in concrete, with brass cap T33N R26W marked :

530 529

from which!

A 9" fir mkd. "14 529 BT" bears N701/2° E 86 Lks. A B"fir mkd. " "/4 S30BT" bears : 73°W 421Ks.

Found: BLM brass cap mkd. as described, from which: 14" willow stump bears N 71°36'E 17 1ks. 20" tamarack stump bears AS3°30'E' 37 /ks. (Scribed) 15" fir with scribing bears N70°25'E BGIKs.



## **SKETCH OF CORNER**

CERTIFICATION

certify the information shown herein is true and correct.

Smith

Smith Surveyor & Seal

Date: 1/2 0/81 Reg. No. 4:405

nployer: Smith Surveying Co.

Sec. 30#29 Office of Clerk and Recorder, County of Lincoln \_\_ . This "corner record was filed for record on the March and \_ day of 19🛱 was noted on the cross-indet plat and is assigned page No. 1559 Eleanor L. Taughn by book No. Z T-5 T. 3.3N R.26W PMM

· corner this sheet