INCTOLICTIONS

- Original and or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- Description of monument and accessories set to perpetuate the corner position.
- Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana,
- 6. Fill in Cross Index & Section Diagram at bottom of sheet

CERTIFIED CORNER RECORDATION

Corner To Section 3, 4, 9 \$10 T. 33N R. 26W P.M.M. Lincoln. County

G10 Record: Set limestone 16"x12"x6" 11" in the ground,

mkd. with 5 notches on South & 3 notches on East edge,


from which:

9" Tamarack bears N71°E 42 lks., mkd." T33NR26WS3BT",
9" Tamarack bears S14°E SS lks., mkd. "T33NR26WS10BT"
12" Tamarack bears SS4°W 3S lks., mkd. "T33NR26WS9BT"
16" Tamarack bears N6S°W 15 lks., mkd. "T33NR26WS4BT"

BLM Record: Set brass cap, mkd. as shown below, with collar of stone, from which:

6" Fir bears NSIE 31 lks., mkd. "T33NR26WS3BT"
7" Fir bears SSI/2" E 28 lks., mkd. "T33NR26WS10BT"
6" Pine bears S78" 41 lks., mkd. "T33NR26WS9BT"
6" Fir bears N44°W 35/ks., mkd. "T33NR26WS9BT"

Found: Monument & Accessories per BLM Record.



SKETCH OF CORNER

CERTIFICATION

certify the information shown herein is true and correct.

Signature Ground Party ろこん、 Sm / ナル

terrify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., 14.D.A.)

Date: 11/19/82 Reg. No. 47405.
Employer: Smith Surveying Co.

was noted on the cross-index plat and is assigned page No. ______, in

Eleanor L. Vaughw by Betty & County Official County

Cross Index No. E-13 T. 33N R. 26W! PMM

S-A-S110

book No.

· uns sheet.