ent data which can best be shown in a sketch example, corner marking

## **CERTIFIED CORNER RECORDATION**

Corner West 1/4 Section 6 only T. 33N R. 26W P.M.M. Lincoln

GLO Record: Set limestone 15"x 8"x6", 10" in the ground, mkd. "1/4" on W. face, from which: 6" Spruce, mkd. "/4 56 BT" bears 515°45'E 33 1ks. 18" Tamarack, mkd. "/4 SIBT" bears 526°W 42 1Ks.

Found: Limestone 12"x5"x6", mkd. "/4" on West face, firmly set in the ground, from which: 6" diam. dead spruce lying face down, scribing visible uprooted base of tree bears 5/6° E 22'. Tamarack in SW quadrant is gone.

New Monumentation: At the location mkd. by the stone, I set a 2"diam. aluminum monument with 3"cap mkd. as Shown below; buried stone alongside monument, and raised mound of stone around cap. 15" Spruce scribed "W/456BT" bears NG8" E 14.73 12" Sprace scribed "W/4 SGBT" boars SGSE 10.97



## **SKETCH OF CORNER**

	CERTIFICATION
1,	
certify the li	ormation shown herein is true and correct.
	Signature Ground Party Chief
.گ.،	R. Smith
by me or t	is Corner Record correctly re-resents work performation by direction in compliance with the "Corn
Recordation	اردر (70-22-101, et seq., M.D.A.)
	R Smith
. ,	Signature of Surveyor & Seai
	8/ Reg. No. 475/05
Employ 'r: _	Smith Surveying Co.

Office of Cerk and Recorder, County of Lincoln	This "corner	Sec. 6	
record" was filed for record on the July 28th	· .1		<del></del> -
was noted on the cross-index plat and is assigned page No	1721 in 14	)- <del>S</del> -	6-
book No County	official appeter	<b> </b>	<del></del>
Cross Index No.		o cenner	this shee