ries set to perpetuate the corner position

Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
Fill in Cross Index & Seciton Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION


1/4 Corner Common to Sections 758 T. 33N R. 26W P.M.M. Lincoln

GLO Record: Set quartzite stone 18x10x6 ins. 12" in the ground mkd. "'4" on W. face, from which: A 4" pine mkd. "1/4 5 7 BT" bears N10°W 14 1ks. A 5" tamarack mkd. "1/4 SBBT" bears NS716"E B /ks.

Stone as described by 620, firmly set, from Found: which !

> 14" Tamerack, face overgrown, bears NS7°E 10" Pine, face overgrown, bears N10°W I did not consider it necessary to open either of the trees to prove the corner.

New Monumentation: At the location mkd. by the stone, I set a 2" diam. aluminum monument with 3" cap stamped as Shown below. Because both bearing trees are alive and healthy, I did not mark any other trees. Buried original stone alongside monument.



## SKETCH OF CORNER

| lion shown | herein | is true | and | correct |
|------------|--------|---------|-----|---------|

|                     | Signature Ground Party Colof                 |     |
|---------------------|--|-----|
| 1. S.R.             | Smith  |     |
| certify that this C | orner Record correctly represents work peri- | OLL |

CERTIFICATION

Date: 1/19/82 Reg. No. 4740.5

|  |                      | . 4            |        |
|--|----------------------|----------------|--------|
| Office of Clerk and Recorder, County     | of Lincoln           | This ''corner  | Sec. 7 |
| record" was filed for record on the $\_$ | July 28th            | day of 19&     |        |
| was noted on the cross-index plat and    | is assigned page No  | 724, in        | -5-17  |
| book No.                                 | Eleanor L. Vaughn by | Betty L. Conas |        |
|  | County Offi          | cial deputy    |        |

G-5 T. 33N R. 26W PMM

certify the informa

· corner this sheet

8