· •				
INSTRUCTIONS				
<ol> <li>Original and/or subsequent record used to evaluate the corner position.</li> <li>Description of evidence found, note discrepancies in the record, state microrners.</li> </ol>		t or obliterated		
<ol> <li>Description of monument and accessories set to perpetuate the corner;</li> <li>Sketch or corner, show all pertinent data which can best be shown it</li> </ol>		rner marking.		
topography ties, position of accessories, etc.  5. Certification must be signed and sealed by Registered Land Surveyor in				
6. Fill in Cross Index & Seciton Diagram at bottom of sheet.		<u>.</u>		
CERTIFIED CORNER RECO	RDATION			
1/4 Corner Common To Sections 9 & 10 T. 33N R. 26	<u>ω</u>	Lincoln	County	
· BIM & GLO Record (GLO IN parent	thesis ):	•		
The 1/4 sec. cor. of secs. 9 and 10, mo	onumented wiset, mkd. 1/4	th a	•	
the W. face, and witnessed by the remain original bearing trees.				
At the corner point		*		
Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. in the ground, with brass cap mkd.	. diam., 24	ins.	. ,	
T33N R26W 1/4				
s 9 s 10				
1967				
from which	·			
The original bearing trees:	:	74 A		
A pine, 8 ins. diam., bears S. 65 dist., mkd. 1/4 S10 BT. (Record)	5° E., 17 lks	s	٠	
A tamarack, 5 ins. diam., bears S dist., mkd. with an overgrown bla	5. 78° W., 10 aze. (Record	6 1ks.		
The new bearing tree:		1		
A larch, 9 ins. diam., bears S. 7 dist., mkd. 1/4 S10 BT.	73½° E., 50 :	lks.		
Bury the original stone alongside th	ne iron post			
<b>P</b> 1				
Found monument and accessories per Bl. 12" BLM Tamarack with scribing bears				
- 12 82.71: Tamarack WITH SCRIBING DEARS	3 /3/2 /_	CERTIFICATION		
	I	ation shown herein is true and	correct.	
7334 R26W		Signature Ground Party Chief  I. S. Mith  certify that this Corner Record correctly represents work performed		
59 510	by me or under	rner Record correctly represent by direction in compliance of (70-22-101, et sai), M.D.A.)		

