Description of monument and accessories set to perpetuate the corner position.
Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking topography ties, position of accessories, etc.

5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana 6. Fill in Cross Index & Seciton Diagram at bottom of sheet.

enation.

CERTIFIED CORNER RECORDATION

Corner: 1/4 Common To Sections 17520 T. 33N R. 26W P.M.M. Lincoln

Set Limestone 24" X8" X8" 18" in the ground, mkd. "1/4" on North fan GLO Record: from which!

12" for mkd. "14 S 17 BT" bears N 1012°W 33 1ks.

10" for mkd. "14 520 BT" bears 5301/2" = 371/kg

Found: "Limestone per record, stone tipped to West, but base appears to be IN original position.

A 15" Fir with overgrown face bears 532°E 23.15'

A 24" Fir with overgrown face bears N10°W 23.00'

It was not deemed necessary to open the bearing trees to prove the cong

At the position marked by the stone's base, I set a New Monumentation: Standard 2" diameter aluminum monument with 3" cap stamped as shown below. Buried store alongside monument and raised a mou, of rock around corner.

> Because both bearing trees are alive and healthy, no additional trees were scribed for this corner.



SKETCH OF CORNER

CERTIFICATION				
I,				
certify the Information shown herein is true and correct.				
Signature Ground Party Calc.				
I. S. R. Smith				
certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)				
SR Smith				
Signature of Surveyor & Seal				
Date: 1/12/82 Reg. No. 4740 5				

Employer: Smith Sarvening

		1	-		
Office of Clerk and Recorder, County	in Lincoln	This ''corner	Sec. 17 \$ 20		
•		_		, <u> </u>	
record" was filed for record on the	July 28th	day of 19&?	 	-+	 -
was noted on the cross-index plat an		748, in	- IS /	7+	-1/-
book No.	Eleanor L. Vaugher L. County Off	ey Bettyl Conces	S 2	-	-4-
)			
	Cross Index No	T. 33N R. 26WPMM	• - corner	this st	heel

corner this sheet