INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

1/4 Corner Section 18 T. 33N R. 26W P.M.M. Lincoln County

BLM + GLO Records: (GLO in parenthesis)

The 1/4 sec. cor. of sec. 18, T. 33 N., R. 26 W., only, monumented with a sandstone, 15 x 10 x 4 ins., firmly set in the ground and mkd. 1/4 on the W. face.

from which the original bearing trees:

A larch, 24 ins. diam., bears N. 27° E., 95 lks. dist., with scribing 18 B visible. (Record)

A larch, 32 ins. diam., bears S. 12 3/4° W., 30 lks. dist., with scribing 1/4 S13 visible. (Record)

At the corner point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in concrete, with brass cap mkd.

T33N
1/4
R27W | R26W
S 18
1961

from which

A pine, 6 ins. diam., bears S. 70 1/2° E., 17 lks. dist., mkd. 1/4 S18 BT.

Bury the original stone alongside the iron post.

Set a wooden post, 4 ft. long, 4 ins. diam., in the ground alongside the iron post.

See Reverse Side for Evidence Found.



SKETCH OF CORNER

CERTIFICATION

I. _____ certify the information shown herein is true and correct.

Signature Ground Party Chief

I. S R Smith certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

S R Smith
Signature of Surveyor & Seal

Date: 2/1/82 Reg. No. 4740 S

Employer: Smith Surveying Co.

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the July 28th day of 1982 was noted on the cross-index plat and is assigned page No. 1751, in book No. _____

Eleanor L. Vaughn by Betty L. Conces deputy
County Official

Cross Index No. _____ T. 33N R. 26W PMM

Sec.



or this sheet

Evidence Found:

BLM Brasscap per BLM corner Records.

34" GLO Tamarack BT bears S13°W 30 lks
scribing visible

4" BLM Pine BT bears S70°E, 16 lks.

5" BLM Pine BT bears N77°W, 9½ lks.