1. Original and/or
2. Description of e ...tablishing lost or obliterated corners.
3. Description of monument and accessories s... perpetuate the corner position.
4. Sketch or corner, show all pertinent data ...ich can best be shown in a sketch example, corner marking, topography ...es, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner Secs 22, 21, 28, + 27 T. 33N R. 26W P.M.M. Lincoln County

BLM + GLO Records. (GLO Records in parenthesis)

The cor. of secs. 21, 22, 27 and 28, monumented with a lime-stone, 6x10x20 ins., firmly set, mkd. with 2 notches on the S. face and 3 notches on the E. face.

from which the remains of the original bearing trees:

A larch, 18 ins. diam., bears N. 29¾° E., 43 lks. dist., with scribing burned. (Record)

A fir snag, 10 ins. diam., bears S. 46° E., 84 lks. dist. with scribing burned. (Record)

A fir stump, 14 ins. diam., bears S. 32½° W., 19 lks. dist., with scribing burned. (Record)

A fir stump, 17 ins. diam., bears N. 35¼° W., 34 lks. dist., mkd. S21 BT. (Record: N. 37¼° W., 34 lks. dist.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, in concrete, with brass cap mkd.

T33N R26W

S21	S22
S28	S27

1960

from which

A larch, 5 ins. diam., bears N. 22° E., 19 lks. dist., mkd. T33N R26W S22 BT.

A larch, 6 ins. diam., bears S. 41¾° E., 56 lks. dist., mkd. T33N R26W S27 BT.

A larch, 6 ins. diam., bears S. 25¼° W., 30 lks. dist., mkd. T33N R26W S28 BT.

See Reverse Side for Evidence Found



SKETCH OF CORNER

CERTIFICATION

I, _____ certify the information shown herein is true and correct.

Signature Ground Party Chief

I, S R Smith certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

S R Smith
Signature of Surveyor & Seal

Date: 2/1/82 Reg. No. 4740S

Employer: Smith Surveying Co.

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the July 28th day of 1982 was noted on the cross-index plat and is assigned page No. 1769, in book No. _____

Eleanor L. Vaughn by Betty L. Conces deputy
County Official

Cross Index No. R-13 T. 33N R. 26W PMM

Sec.

S21	S22
S28	S27

or this sheet

Evidence Found:

BLM Brasscap per BLM Records

9" Tam., bears S 74° W, 42.3' } BLM Trees, Scribing Visible
8" Tam. bears N 46° W, 34.6' }
6" Tam. bears N 20° E, 12.5' }

18" Oak Tam. bears N 29° E, 28.5' - Scribing Visible