

- INSTRUCTIONS
1. Original and/or subsequent record used to evaluate the corner position.
  2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
  3. Description of monument and accessories set to perpetuate the corner position.
  4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
  5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
  6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

$\frac{1}{4}$  Corner Common to S21 + S28 T. 33N R. 26W P.M.M. Lincoln Count  
BLM + GLO Record (GLO Record in parenthesis)

The  $\frac{1}{4}$  sec. cor. of secs. 21 and 28, monumented with the remains of the original wooden post corner, scribed  $\frac{1}{4}$  S.

from which the remains of the original bearing trees:

A larch, 18 ins. diam., bears N.  $37\frac{1}{4}^{\circ}$  W., 53 lks. dist., with scribing overgrown. (Record)

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 27 ins. in the ground, in concrete, with brass cap mkd.

T33N R26W

$\frac{1}{4}$  S21  
S28

1961

from which

A larch, 5 ins. diam., bears N.  $6^{\circ}$  E., 24 lks. dist., mkd.  $\frac{1}{4}$  S21 BT.

A larch, 6 ins. diam., bears S.  $57^{\circ}$  W., 16 lks. dist., mkd.  $\frac{1}{4}$  S28 BT.

Bury the remains of the original wooden post corner alongside the iron post.

Set a wooden post, 5 ft. long, 5 ins. diam., in the ground alongside the iron post.


### Evidence Found:

BLM Brass cap per BLM Records.

24" GLO Tam. B.T. w/scribing overgrown bears N38°W, 53 lks.

8" Tam. B.T. bears S57°W, 16 lks.

8" Tam. B.T. bears N6°E, 24 lks.



SKETCH OF CORNER

### CERTIFICATION

I, \_\_\_\_\_, certify the information shown herein is true and correct.

Signature Ground Party Chief

S. R. Smith

I certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

Signature of Surveyor & Seal

Date: 2/1/82 Reg. No. 47405

Employer: Smith Surveying Co.

Sec. 21 + 28

	Sec 21	
	Sec 28	

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the July 28<sup>th</sup> day of 1982 was noted on the cross-index plat and is assigned page No. 1770, in book No. \_\_\_\_\_

Eleanor L. Vaughn by Betty L. Conces  
County Official deputy

Cross Index No. R-11 T. 33N R. 26W P.M.M.

this sheet