

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

4 Corner Common to Sec 26 + 25 T. 33N R. 26W P.M.M. Lincoln County
BLM + GLO Record: (GLO Record in Parenthesis)

The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented with a granite stone, 9x10x12 ins., firmly set in the ground and mkd. $\frac{1}{4}$ on the W. face.

from which the original bearing trees:

A pine, 9 ins. diam., bears S. 62° E., 3 lks. dist., with scribing overgrown. (Record:)

A larch, 14 ins. diam., bears N. 50° W., 42 lks. dist., with scribing overgrown. (Record: N. 51 $\frac{1}{4}$ ° W., 42 lks. dist.)

At the corner point:

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, in concrete, with brass cap mkd.

T33N R26W

S26 | S25

1960


from which

A fir, 7 ins. diam., bears N. 76 $\frac{1}{2}$ ° E., 55 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

Bury the original stone alongside the iron post.

Raise a mound of stone, .3 ft. base, 2 ft. high, W. of the iron post.

Evidence Found: 8" BLM Fir Bears N 77° E 54 3/4 Lks.
 12" GLO Tamarack at N 50° W 42 Lks.
 8" Fir (fallen) at S 62° E 3 Lks.



SKETCH OF CORNER

CERTIFICATION

I, Thomas Van Slyke
 certify the information shown herein is true and correct.

Signature Ground Party Chief

I, S R Smith
 certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

Signature of Surveyor & Seal

Date: 2/1/82 Reg. No. 47405

Employer: SMITH SURVEYING

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the July 28th day of 1982 was noted on the cross-index plat and is assigned page No. 1773, in book No. _____

Eleanor L. Vaughn by Betty L. Conces
 County Official deputy

Cross Index No. T-21 T. 33N R. 26W P.M.M.

Sec.

• - corner this sheet