INSTRUCTIONS

- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- a rescription or monument and accessories set to perpendic the corner position.

 4. Sketch of corner, show all perfined data which can best be shown in a sketch example, corner marking, topography lies, position of accessories, etc.
- 7. Certification must be signed and scaled by Registered Land Surveyor in State of Montana

CERTIFIED CORNER RECORDATION

4 Corner common to Sec. 26+35 T. 33N R 26W PMM Lincoln BLM+GLO Record: (GLO Record in Parenthesis)

The \(\frac{1}{4}\) sec. cor. of secs. 26 and 35, monumented with a limestone, 6xlOxl2 ins., firmly set and mkd. \(\frac{1}{4}\) on the N. face.

from which the original bearing trees:

A fir, 16 ins. diam., bears N. 17° E., 41 lks. dist., with scribing overgrown. (Record: N. 18° E., 41 lks. dist.)

A fir, 15 ins. diam., bears S. $4\frac{1}{2}$ ° W., 55 lks. dist., with scribing overgrown. (Record: N. $2\frac{1}{4}$ ° W., 55 lks. dist.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

T33N R26W

Bury the original stone alongside the iron post.

Evidence Found:

16" GLO Fir Bears N18"E 41 1ks. 16" GLO Fir Bears S21/4°W 55 1ks.



SKETCH OF CORNER

cord correctly represents work performed SMITH SURVEYING CO.

| Office of Clerk and Recorder, County of | of Lincoln | This ''corner | Sec. |
|---|------------------------------------|---------------------|-------------|
| | | | 1 |
| record" was filed for record on the | July 281h | day of 198 <i>4</i> | \vdash |
| was noted on the cross-index plat and i | is assigned page No/ | 1 <u>785</u> , in | |
| book No. | Eleanor L. Vaugen by County Off | Betty L. Conces | |
| • | | Icial deputy | |
| | Cross Indias No. V-19 | 733N 256 | • 4 . |

per this sheet