

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

$\frac{1}{4}$ Corner common to S 34 + S35 T. 33N R. 26W P.M.M. Lincoln County
BLM + GLO Record: (GLO Record in Parenthesis)

The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, determined from the remains of the original bearing trees: (Larch and Fir)

A fir, stump, 21 ins. diam., bears S. $65\frac{1}{4}^{\circ}$ E., 41 lks. dist., mkd. BT. (Record)

A larch stump, 20 ins. diam., bears S. 68° W., 46 lks. dist., mkd. $\frac{1}{4}$ S34 BT. (Record: S. $71\frac{1}{4}^{\circ}$ W., 46 lks. dist.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground in concrete, with brass cap mkd.

T33N R26W.
S34 S35
1960

from which

A fir, 10 ins. diam., bears S. $46\frac{1}{2}^{\circ}$ E., 116 lks. dist., mkd. $\frac{1}{4}$ S35 BT.

A fir, 8 ins. diam., bears S. $29\frac{1}{2}^{\circ}$ W., 44 lks. dist., mkd. $\frac{1}{4}$ S34 BT.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the iron post.

Evidence Found:

Monument and Accessories as per BLM Record.

See Reverse Side for found B.T.'s



SKETCH OF CORNER

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the July 28th day of 1982, was noted on the cross-index plat and is assigned page No. 1005, in book No. Eleanor L Vaughn by Betty L Conces
County Official Deputy

Cross Index No. X-17 T. 33N R. 26W PMM

CERTIFICATION
I, Thomas Van Slyke, certify the information shown herein is true and correct.

Signature Ground Party Chief

I, S.R. Smith,


certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

S.R. Smith

Signature of Surveyor & Seal

Date: 2/1/82 Reg. No. 47405

Employer:



• For this sheet

- 20" GLO B.T. Stump with scribing bears S $65\frac{1}{4}$ 'E 41 Lks.
14" BLM Fir bears S $29^{\circ}30'W$ 44 Lks.
14" BLM Fir bears S $45^{\circ}30'E$ 115 $\frac{1}{4}$ Lks.

