Original and/or subsequent record used to evaluate the corner position

2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

- corners.

 3. Description of monument and accessories set to perpetuate the corner position.

 4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

 6. Fill in Cross Index & Seciton Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner To Sections 19 & 30 T. 33N R. 26W P.M.M. Lincoln County & Sections 24\$25 T. 33N. R 27W

This corner was never set by 610 or BLM.

Set corner by single proportion between Witness corners North. and South of 1/4 corner.

Set Standard 2" diam. aluminum monument with 3" cap marked as shown below. Conner is 17 feet west of a N-S fenceline.

A 14" cottonwood scribed "S24BT" bears N45°W. 54.50'

powerpole bears 52°W 98.10'

No other reference marks available - Corner falls a very boggy area.



SKETCH OF CORNER

	CERTIFICATION
1	·
•	ertify the information shown herein is true and correct.
•	Signature Ground Party Chief
	_S.R. Smith
t	ertify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (70-22-101, et. seq., M.D.A.) Signature of Surveyor & Seal
ı	Date: 1/18/82 Reg. No. 47405
1	Employer: Smith Surveying Co.

Office of Clerk and Recorder, County of		•
record" was filed for record on the	July 23th	day of 1983
was noted on the cross-index plat and i	is assigned page No	/812, in
book No.	Eleanor L. Vaughi	by Betty L. Conces Official deputy
•.		T. 33N R. 26W PMM
	Cross Index No.	T. 33N R. 26W PMM

5 2	4-	5	19	
ऽ ३	5	-5	30	
• - co		this sheet R 26W		