INSTRUCTIONS

- position
- Sketch or corner, show all pertinent data which can best be shown in a sketch example, topography ties, position of accessories, etc.
- ust be signed and sealed by Registered Land Surveyor in State
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

LINCOLN (. m, et à . x R. 26W P.M.M. Corner E 1/16 cor. south side sec. 357 33N .County

RECORD: No previous record of corner on file.

FOUND: Nothing to show evidence of a monumented corner.


SET: A 3" diam, brass cap into a flat exposed stone approx. 8" below the surface of the ground adjacent to a 9" stump, marked as shown and surrounded with a stone collar.


from which

A fir 11" diam., bears N 57°W 4.5' dist., scribed "F 1/16 BT".

A fir 10" diam., bears S 26°E 17.2' dist., scribed "BT".

BT's are painted red.





400

). و) مالاهٔ این د

457°W 10" FIR

SKETCH OF CORNER

CERTIFICATION James W. Reed W. Reef Thomas C. Hill certify that this Corner Record correctly repre-by me or under by direction in compliant Recordation Act." (79-72-101, et seq., M.D.A.) Date: 8/12/82 Reg. No. 5612S 115FS

Office of Clerk and Recorder, County of	LINCOLN .	This "corner	Sec. 32
record" was filed for record on the	OCT 67	day of 1982_	-
was noted on the cross-index plat and is	assigned page No. 2	.038, in	
book No.	Eleanor L. Thugh K	2 Etty L. Conces	
•	County Of	ficial deputy	

33 R 25 PMM corner this sheet