INSTRUCTIONS

d to evaluate the curner position

Serich or corner, show all pertinent data which oursplay lies, position of accessories, etc.

b. Certification must be signed and sealed by Registered Land b

6. Fill in Cross index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

N 1/16 Cor. Sec. 1 Corner_ T. 33N R. 26W LINCOLN . P.M.M. County


No record or evidence of corner being previously set.

I position corner from found Section and Quarter corners and as shown on the Certificate of Survey as filed and as of record in the Lincoln Co. Courthouse.

I set a 3" alum. cap for corner position, from which:

A 14" communication pole bears N32° W., 79.66° A 14" communication pole bears S.68° W., 118.76° Centerline of the BNRR bears Northwesterly 5.7°

Posted BT, Attention, and Location signs Placed a 6' metal post w/survey monument sticker along side cap.



CYMPAUNICATION Q CERTIFICATION GLENN KNODLE ER.E. A COMMUNICATIVE TOWN. Reg. No. 27345 POLE Employer: ROCKY HOUNTAIN SURVEYORS SKETCH OF CORNER Office of Clerk and Recorder, County of LINCOLN . This "corner record" was flied for record on the ___ NOU 30 - day of 1984 was noted on the cross-index plat and is assigned page No. 2799 Janet BF Siegel by Ketty Concess County Otticial deput book No. T. 33N R. 26W corner this sheet