initality store.

1. Original and/or subsequent record used to evaluate the corner position.

2. Description of processes found, asse discrepancies in the record, state method of exploing lost or obliterated corners.

3. Description of recomment and accessories set to perpetuate the corner position.

4. Sarich or corner, show all perilions data which can best be shown in a sketch example, corner marking, supportably ties, position of accessories, sic.

5. Certification must be signed and sested by Registered Land Surveyor in State of Montans.

6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED	CORNER	RECORDATION
	7 - 1 - 1 - 1	110001101111011

Corner C-S 1/16 Sec. 12 T. 33N R. 26W P.M.M. LINCOLN County


No record or evidence of corner being previously set.

I position corner from found Section and Quarter corners and as shown on the Certificate of Survey as filed and as of record in the Lincoln Co. Courthouse.

I set a 3" alum. cap for corner position, from which:

A 5" fir bears N.25°E., 13.5° scribed C-S 1/16 S12 BT A 6" fir bears N.20°W., 3.0° scribed C-S 1/16 S12 BT

Painted red bands around BT's and painted blazes red.
Posted BT, Attention, and Location signs.
Placed a 6' metal post w/survey monument sticker along side cap.



CERTIFICATION GLENN KNODLE Ŋ certify the information shown heyeln is true and correct. LE" FIR GENE WARREN certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (70-22-10), et seq., M.D.A.) At Gene Wang Date: 10/84 Reg. No. 27345 Employer: POCKY HOUNTAIN SURVEYORS SKETCH OF CORNER Sec. 12 Office of Clerk and Recorder, County of LINCOLN _ . This "corner record" was filed for record on the Nov 30 . day of 195,∜ was noted on the cross-index plat and is assigned page No. _2908 Janet BF Sugil by Betty Concer Country Official deputy book No. . Cruse Index No. H23 T. 33N H. 26W PMM · corner this sheet