INSTRUCTIONS

equent record used to evaluate the curner position.

see found, note discrepancies in the record, state method of establishing lost or oblitera

Original and/or subsequent record used to evaluate the curner position.
 Description of extrance found, note discrepancies in the record, state method of corners
 Description of monument and accessories set to perpetuate the curner position.

Secretarion of monument and accessories set to perpetuate the corner position.
 Sector or corner, show all pertinent data which can best be shown in a sketch example, corner marking topography ties, position of accessories, etc.

5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

6. Fill in Cross index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner C-E 1/16 Sec. 14 T. 33N R. 26W P.M.M. LINCOLN County

No record or evidence of corner being previously set.

I position corner from found Section and Quarter corners and as shown on the Certificate of Survey as filed and as of record in the Lincoln Co. Courthouse.


I set a 3" alum. cap for corner position, from which:

An 8" fir bears N.42°E., 29.0' scribed C-E 1/16 S14 BT A 10" tamarack bears S.64°E., 20.8' scribed C-E 1/16 S14 BT

Painted red bands around BT's and painted blazes red.

Posted BT, Attention, and location signs.


Placed a 6' metal post w/survey monument sticker along side cap.



CERTIFICATION

information shown herein is true and correct.

KNODLE



certify that this Corner Record correctly represents work performed by me or under by direction in compilance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

H. Line Watter

Signature of Surveyor & Soul

Signature of Surveyor & Sea Date: 10/84 Reg. No. 27345

GLENN

Employer: POCKY HOUNTAIN SURVEYORS

SKETCH OF CORNER

corner this sheet