

INSTRUCTIONS

Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

- 3. Description of monument and accessories set to perpetuate the corner position.

 4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

T. 32 N R. 27 W P.M.M. LINCOLN Corner C C SEC. 5 & SEC.

County

1.RECORD: ORIGINAL 1929 SET A IRON POST 3° LONG 2° DIAM. 28" IN THE GROUND FOR THE CLOSEING COR.OF SEC. 5 AND 6 WITH BRASS CAP MARKED

T33N R27W T32N | R27W

FROM WHICH:

A TAM. 8" DIAM. BEARS S 39 45' E 29 LKS. DIST. MARKED T 32 N R 27 W S 5 C C BT.

A FIR 8" DIAM. BEARS S 9° 30' W 13 LKS. DIST. MARKED T 32 N R 27 W S 6 G C BT.

- 2. FOUND: BRASS CAP AS SHOWN ABOVE, AND SEC. 6 BT NOW 14" DIAM BEARING S 11° W 8.15 FT. DIST. NO EVIDENCE OF SEC. 5 BT WAS FOUND.
- 3.ACCESSORIES: A WHITE FIR 14" DIAM BEARS S 86°30' E 5.65 FT. DIST. MARKED T32N R27W S 5 BT.
 ALSO SET A 6' STEEL POST APPROX. 3.0' NORTH OF MONUMENT MAINTAINED BT'S WITH SIGN'S AND PAINT.

