

## INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner Corner 1 HES 1217 T. 32 N. R. 28 W. P.M.M. Lincoln County

1. 1923 USDA Field Notes, J. F. Pfau: Place a small stone marked with a cross (x) under a sandstone 36 x 18 x 8 ins., 26 ins. in the ground, marked 1 H.E.S. 1217 on N. face, and a cross (x) on top for the exact cor. point, from which  
 A cross (x) on a yellow pine tree 30 ins. dia. bears N.  $38^{\circ}00'$  E. 23 lks. dist.  
 A cross (x) on a tamarack tree 24 ins. dia. bears S.  $75^{\circ}45'$  W. 122 lks. dist., each blazed and scribed 1 H.E.S. 1217 B.T.  
 Raise a mound of earth and stone 4 ft. base, 2 ft. high N. of cor.
2. I found a firmly set stone, 12 x 8 ins., 18 ins. above ground with visible scribing "1 HES 1217" on the north face and an "x" at top center. There is a 2 ft. mound of stone north of the corner. From the stone:  
 A larch snag, 11 ins. diam., bears N.  $80^{\circ}$  E., 14.4 ft. dist. scribed "1 HES 1217 BT"


This tree does not fit the record bearing trees for this corner. After examining the record it was discovered that the trees reported for this corner were also reported for Corner 9, HES 1217. Trees matching the record were found at corner 9. It is therefore believed that the bearing trees for this corner were never accurately reported. Using the set stone as evidence, I accept this as the original position for Corner 1 even though the bearing tree found does not match record.

A 1982 U.S. Army Corp of Engineers (C.O.E.) Monument, an aluminum post with a 3 1/4 in. diam. aluminum cap marked "1207/1", bears S.  $47^{\circ}14'59''$  W., 4.27 ft. dist., from the found stone. The C.O.E. did not tie their survey to HES 1217 and therefore this monument fall on National Forest property. I do not accept the C.O.E. monument as a representation of the true property boundary.

3. I rebuilt the mound of stone. Set a galvanized steel guard post with a Survey Marker decal attached, 2 ft. from the corner. I marked and scribed two bearing trees:  
 A douglas fir, 8 ins. diam., bears N.  $38^{\circ}$  E., 33.0 ft. dist., scribed 1 HES 1217 BT.  
 A douglas fir, 16 ins. diam., bears N.  $44^{\circ}$  W., 22.7 ft. dist., scribed 1 HES 1217 BT.  
 I painted red bands around bearing trees and attached BT and Land Survey Monument signs. Set a galvanized steel guard post, with a Survey Marker decal attached, 1 ft. northwest of the monument.

This corner is approximately 250 ft. south of Highway 37 on a 40% side slope in a mixed douglas fir and larch stand.

NOTE: This is corner 1 of Tract 5, which was created as a remainder of HES 1217, as referred to in Warranty Deed, Book 35, Page 652.



SKETCH OF CORNER

## CERTIFICATION

I, Robbin L. Glazier  
 certify the information shown herein is true and correct.

Robbin L. Glazier  
 Signature Ground Party Chief

I, Alvah F. Hughes  
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Alvah F. Hughes  
 Signature of Surveyor & Seal

Date: 11/05/87 Reg. No. 7322-S


Employer: U.S. Forest Service

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on Nov. 18, 1987

was noted on the cross-index plat and is assigned page No. 3715, in book No. \_\_\_\_\_

Cross Index No. 1-HES 1217 T. 32N R. 28W P.M.M.

Sec. 18



• - corner this sheet

# INSTRUCTIONS TO SURVEYORS FOR COMPLETION OF CERTIFIED CORNER RECORDATION FORMS

## I. ORIGINAL AND/OR SUBSEQUENT RECORD:

This item should describe or quote those portions of the original or subsequent record which were used in evaluating the corner position. The original record will usually be the General Land Office field notes. Subsequent record can come from several sources: Previously filed corner records, maps and plats, private and public records, etc. Some of the subsequent record, even though not in the public record, but known to have validity by the surveyor, may be quoted and appropriately noted.

The record data helps support the reestablished corner position because it clearly shows what history the surveyor based his corner position on. In some cases, however, the record may be unknown or not pertinent. A statement to that effect should appear on the corner record.

## II. DESCRIPTION OF EVIDENCE FOUND OR METHOD OF LOCATING CORNER POSITION:

This item will describe the original or subsequent record evidence found. If portions of the found evidence cannot be reconciled with the record, then the disregarded record should be noted, and, if possible, an opinion as to its cause narrated.

If no physical evidence of the original or subsequent monuments and accessories can be found, then the method used to reestablish the lost or obliterated corner (single proportion, fence intersection, parol evidence, terrain calls, centerline of road, etc.) shall be indicated.

## III. DESCRIPTION OF MONUMENTS AND ACCESSORIES SET TO PERPETUATE THE CORNER POSITION:

This item should list all details about the corner and its location which will help exclusively identify the corner position; including size and type of monument, how marked if not shown in sketch, and distinguishing topographic calls which help locate the corner. In many cases, instructions on how to find the corner should be included.

References or ties to other corners are optional and may be drawn on the face or back of the corner record form, or references to Certificate of Survey may be made. Separate drawings may be attached to the corner form.

If state plane coordinate values for the corner position are shown, then the control upon which they are based should be indicated.

## IV. SKETCH OF CORNER:

This item will usually show how a found or set corner is marked and may also show topography or accessory monuments found or set and their relation to the corner. There is no stipulated format; the sketch could be transcribed field note entries.

## V. CERTIFICATION:

The name and signature of the ground party chief is optional.

The Surveyor who performed or directed the field work which is depicted on the "Certified Corner Record" shall sign and affix his seal in the Certification.

The employer blank is optional but useful in tracking down original field note data or adjacent record if, in the future, questions arise about the corner.

## VI.

The Cross Index at the bottom of the page should be completed by the Surveyor. Only the single Township Index where the corner is filed shall be completed.

The lower righthand corner is a corner location diagram and should have the pertinent section filled in at the top and a closed circle indicating the appropriate corner position in the section filled in. This is intended to be an aid in searching the "Record" once it has been filed.

