INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner position.
 Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- corners.

 3. Description of monument and accessories set to perpetuate the corner position.

 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.


 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

32 N., 28 W., P.M.M. C E W 1/64 Sec. 30 Lincoln Corner_ _County

- No previous record.
- II. No evidence on the ground.
- III. At the determined corner position by survey, set a 3/4 ins. dia. aluminum rod, 30 ins. long, 26 ins. in the ground attached 3 1/4 ins. dia. U.S.D.A. Forest Service aluminum cap,



placed a rock collar around monument.

from which

A ponderosa pine, 17 ins. diam., bears $N19^{\circ}E$, 20.5 ft. dist., mkd. C-E-W 1/64 S30 BT. A ponderosa pine, 17 ins. diam., bears $S52^{\circ}W$, 15.4 ft. dist., mkd. C-E-W 1/64 S30 BT.

Painted a red band around each bearing tree and attached "Land Survey Monument" and "Bearing Tree" signs where needed.

Set a guard post with "Survey Marker" and "Property Boundary" decals attached, 3 ft. S. from corner.

Magnetic Declination: East, 19



· - corner this sheet

РММ

CERTIFICATION Gary C. Crismon certify the information shown berein is true and correct. Ronald A. Pearson certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et-seq., M.C.A.) 11/26/90_{Reg. No.} 9008LS U.S. FOREST SERVICE **SKETCH OF CORNER** Office of Clerk and Recorder, County of . This "corner Dec 10, 1990 record" was filed for record on _ was noted on the cross-index plat and is assigned page No. book No. _

Cross Index No.