



CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN) Lincoln County At the section corner common to Sections 10, 11, 14 & 15, T32N, R29W, P.M.M., We find: A 28" tamarack stump, 5 ft.+ high, marked: on NW face "S10 R29-" and on NE face "S11". Note: We did not chop out the other two overgrown faces. (Record: "A tamarack tree, 23" diameter for corner of Secs. 10, 11, 14 & 15; I mark "T32N S11" on NE, "R29W S14" on SE "S15" on SW, "S10" on NW side") from which: A tamarack stump, 6' high, 24" diameter, scribing plain, bears N24° E, 28 links distant. (Record: Tamarack, 24" diameter, bears N23° 30' E, '27 links) and a 20" tamarack stump, 6' high, scribing plain, bears S44° E, 42 links (Record: 15" tamarack bears S45° 30' E, 41 links) No trace of the 3rd BT. (Record: Tamarack, 7" diameter, bears S64°W, 65 links distant) Note: The position for this falls in a skid trail. And a 2 ft. high tamarack stump, 16" diameter, scribing plain, bears N42°W, 58 links. (Record: 24" tamarack bears N 41° 43' W, 57 links)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: May 19, 1966

To perpetuate this corner we create 2 new reference monument trees which bear from the exact center of the corner monument stump as follows:

A 5" Douglas-fir bears S20°W, 59 links distant, and an 8" Douglas-fir bears N56°W 51 links distant both double blazed and scribed "RM".
We placed attention B.T., and location poster signs.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal	I. M. Tillotson, E. Laven, R. Christianson, V. Coble	DIAGRAM OF CORNER:
	certify that the information shown herein is true and correct.	N. TOON ROOM
	Signature of Ground Party Chief	3 10 5 11
	I. Stanley J. Skousen	5 15 5 14
	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.	
	Stanley J. Skousen Stanley I Rouse	= Corner recorded on the sheet
•	Signature of Surveyor	
	253 2 \$	April 1
•	Registration Number	,

Cross Index No. J-/Z T.

Office of Clerk and Recorder, County of ...

assigned page No.

This "corner record" was filed for record on the day of