

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner $W\frac{1}{4}$ Cor. Sec. 31 T. 32N R. 29W P.M.M. Lincoln County

Original GLO Notes: Set a trachite stone 26x5x5 in. 19" in the ground, for $\frac{1}{4}$ Sec. cor, mkd. $\frac{1}{4}$ on W. face; from which:

A fir 10" bears $N42^{\circ}E$ 112 lks., mkd. $\frac{1}{4}$ S31 BT.
 A fir 12" bears $S84^{\circ}45'W$ 45 lks., mkd. $\frac{1}{4}$ S36 BT.
 (1904 Paul S.A. Bickel)

Dependent Resurvey: The $\frac{1}{4}$ Sec. Cor.; a broken slate stone, marked and witnessed as described in the official record.

In place of stone; set an iron post, 3 ft. long, 1" diam., 28" in ground, for $\frac{1}{4}$ sec. cor., w/ brass cap mkd:

$\frac{1}{4}$
 S36 | S31
 1940

(1940 by Ranney Y. Lyman, Cadastral Surveyor)

Found $2\frac{1}{2}$ " brass cap on 1" iron pipe monument for $\frac{1}{4}$ sec. cor. mkd. incorrectly: Cor. mon. badly bent over.

From which:

A fir 26" bears $S88^{\circ}W$ 30.0 feet, blaze & scribe partly visible. $\frac{1}{4}$
 S31 | S36
 1940


New BT Set: A 7" pine bears $S74^{\circ}E$ 8.0 feet, mkd. $\frac{1}{4}$ S31 BT.

Built a rock cairn around mon. 3' diam. and cleared ground to 6' diam. Painted and signed all BT's as per spec's. Set a steel sign post near corner.

Decl. $20^{\circ}E$ assumed.

Cor. Mkd.: (Incorrectly)

$\frac{1}{4}$
 S31 | S36
 1940



SKETCH OF CORNER (SEE ABOVE)

CERTIFICATION	
I, <u>Robert E. Findorff</u>	
certify the information shown herein is true and correct.	
Signature Ground Party Chief	
I, <u>Robert E. Findorff</u>	
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (20-2-101 et seq., M.C.A.)	
Signature of Surveyor & Seal	
Date: <u>11/13/87</u>	Reg. No. <u>3976 ES</u>
Employer: <u>Self</u>	

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on Nov 16, 1987


was noted on the cross-index plat and is assigned page No. 3693 in

book No. _____

Cross Index No. X-1 T. 32N R. 29W P.M.M.

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

Sec. 31, T32N, R29W



• - corner this sheet