

CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Quarter corner common to Sec. 3 and 10, T32N, R30W, MPM
 Found Brass Cap firmly set and marked (Record - Set iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked)
 S3
 1940
 A fir, 24 ins. diam. bears N5°0'W, 35 lks. dist., decayed stump with scribing visible (Record - A fir, 24 ins. diam., bears N5°0'W., 35 lks. dist., marked $\frac{1}{4}$ S3 BT.
 A larch, 16 ins. diam. bears S14°0'E. 21 lks. dist., down and decayed (Record - A tamarack, 16 ins. diam., bears S14°0'E., 21 lks. dist., marked $\frac{1}{4}$ S10 BT.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: July 19, 1973

New BT's
 A Spruce, 9 ins. diam., bears S9°0'E - 11 lks. dist., marked FS RM
 A Spruce, 14 ins. diam., bears N5°0'E - 32 lks. dist., marked FS RM
 I placed BT and Attention signs and red paint on BT's and at corner.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original G.L.O. field notes)

Surveyor's Seal


I, Gary L. Wohlwend
 certify that the information shown herein is true and correct.

Gary L. Wohlwend
 Signature of Ground Party Chief

I, Stanley J. Skousen
 certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Stanley J. Skousen
 Signature of Surveyor

DIAGRAM OF CORNER:



• = Corner recorded on the sheet

2532-S
 Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 12th day of October 1973, was noted on the cross-index plat and is

assigned page No. 293, in book No. 1

ELEANOR L. VAUGHN
 County Official

Cross Index No. E-15 T-32 R-30 Mer.