

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner Sec. 5, 6, 7, & 8 T. 32N R. 30W P.M.M. Lincoln County

Original GLO Notes: Set a limestone 18x8x6 in., 12 in. in ground for corner, Sec. 5, 6, 7, & 8, mkd. w/5 notches on S. & E. edges frm which:

A fir 20 in. dia. bears N75 $\frac{1}{2}$ ⁰E 35 lks mkd. T32N R30W S5 BT
 A fir 10 in. dia. bears S79 $\frac{1}{2}$ ⁰E 24 lks mkd. " " S8 "
 A " 10 " " " S46 $\frac{1}{2}$ ⁰W 36 " " " " S7 "
 A Tamarack 36 in. dia. bears N26⁰W 30 lks mkd. T32N R30W S6 BT.
 (1916 by: Mans H. Coffin, Jr., R. Fitzhugh Maclean, James R. Cumming)

Remonumentation Survey: Duane G. Lindenberg, Cadastral Surveyor, 1965)

Found a limestone 18x8x6 in. firmly set and marked w/5 notches on E. & S. edges and witnessed the remains of original bearing trees.

At cor. point set an iron post, 30" long, 2 $\frac{1}{2}$ " dia., 26 in. in ground w/ brass cap mkd: T32N R30W

S6	S5
S7	S8

1965

From which original BT's:

A stump, 18" bears N75 $\frac{1}{2}$ ⁰E 43 lks mkd. T32N R30W S5 BT (Rec. 33lks)
 A fir 16" bears S79 $\frac{1}{2}$ ⁰E 22lks mkd. T32N R30W S8 BT (Rec. 24 lks.)
 A stump 18" bears S46 $\frac{1}{2}$ ⁰W 24 lks mkd. T32N R30W S7 BT (Rec. 36 lks)
 A larch 26" bears N26⁰W 12 lks mkd. T32N R30W S6 BT (Rec. 30 lks)

The new BT's: A fir 15" bears N35 $\frac{1}{2}$ ⁰E 68 lks mkd. T32N R30W S5 BT.

A fir 10" bears S27⁰W 34 lks mkd. T32N R30W S7 BT.

A fir 8" bears N60⁰W 68 lks mkd. T32N R30W S6 BT.

Buried original corner stone alongside iron post.

T32N R30W
S6 S5
S7 S8
1965


Found 3 $\frac{1}{2}$ " Brass Cap on an iron post mon. in rock cairn w/mon. mkd:

Existing BT'S: 16" fir N36⁰E 45.6' blaze & scribe visible.
 15" fir (fallen) S76⁰E 13.9' scribe visible.
 10" fir S27⁰W 22.2' scribe visible.
 12" fir N60⁰W 44.7' scribe visible.
 14" fir stump S49⁰W 15.5' scribe visible.
 28" Fir stump N17⁰W 7.4' scribe visible.

New BT: 12" hemlock S51⁰E 25.3' mkd. T32N R30W S8 BT.

Painted and signed all BT's to meet F.S. Spec.. Set sign post S. of Cor. and built a rock cairn 3' dia. around corner.

Declination assumed 20⁰E.



SKETCH OF CORNER (SEE ABOVE)

Office of Clerk and Recorder, County of Lincoln This "corner

record" was filed for record on Nov 16, 1987

was noted on the cross-index plat and is assigned page No. 3711, in

book No. _____

Grant B. Supel by Bill Supel
 County Official

Cross Index No. E5 T. 32N R. 30W P.M.M.

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

CERTIFICATION

I, Robert E. Findorff
 certify the information shown herein is true and correct.

Signature Ground Party Chief

I, Robert E. Findorff


certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (17-2-101 et seq., M.C.A.)

Robert E. Findorff
 Signature of Surveyor & Seal

Date: 9/12/87 Reg. No. 3976FS

Employer: Self

Sec. 8 T32N R30W



• corner this sheet