	CERTIFIED CORNER R	ECODDATION.
Corner E 1/4		31 W. P.M.M. Lincoln County
	survey by Abram L. Jaqueth: Se cor. marked 1/4 on W. face,	et a sandstone 30x12x10 ins. 22 ins. in from which:
	ım., bears N.65°15'E., 14 lks. dis am., bears S.61°10'W., 10 lks. dis	
II. <u>Found:</u> During a	field search of area, no monume	ent or related accessories were found.
III. Perpetuation: A 1/2 ins. diameter x 3 cap marked as shown	0 ins. long, 24 ins. in the grour	from survey, we set a aluminum pipe, 2 and with a 3 1/4 inch diameter aluminum
,	am., bears N.12°E., 20.90 ft. dis m., bears N.74°W., 13.90 ft. dist	,
Raise a collar of	stone 24 ins. diam. around mor	nument.
	d 6 in. wide red bands to all be and Bearing Tree signs.	earing trees and attached Land
-	ion: 20° East assumed Hand compass and loggers tape	T32N R31W 1/4 S4 S3 7322 LS 2004
Kootenai Surveyors SI Project: Pipe Cr PCTC	Inc., 314 California Av., Libby, M	IT. 59923 (406) 293-4354 CERTIFICATION
11" Hemlock 13.90 ft. N74"W	6" Pine	Signature Ground Party Chief Alvah F. Hughes certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.) Signature of Surveyor & Seal Date: 3/02/2005 Reg. No. 7322-LS Employer: Kootenai Surveyors Inc.
Office of Clerk and Recorder record" was filed for record was noted on the cross—inc book No.	County of Lincoln Thi 186013 BOOK: CCR CCER'S STATE OF MONTANA LINCOLN COUNTY	CRDER SERNIE SERNIE SERVICES

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors