Corner	CERTIFIED CORNER RECORDATION SW 1/16 Sec 4 T 32 N. R. 31 W. P.M.M. LINCOLN County
I. Record:	None
II. <u>Found:</u>	During field search of area no monument or related accessories were found.
Alum. pip	etuation: At a computed point determined from survey, we set a 2 1/2 ins. diam. see 30 ins. long 24 ins. in the ground, with a 3 1/4 in. diam. Alum. cap marked as slow from which:
A G A G	rand fir, 6 ins. diam., bears N.23°E., 9.90 ft. dist., scribed SW 1/16 S4 BT. rand fir, 5 ins. diam., bears S.87°E., 8.20 ft. dist., scribed SW 1/16 S4 BT.
Pain Mon	ited faces red and 6 in. wide red bands to all bearing trees and attached Land Survey ument and Bearing tree signs.
Set	a steel post 2 ft. W. of monument.
Equ	gnetic declination: 18° East assumed  SW 1/16 S4 7322 LS 2005  CONTACTOR OF THE PROPERTY OF TH
Koote KSI Project: P	Signature Ground Party Chief  Alvah F. Hughes  certify that this Corner Record correctly represents work performed by me or under my direction in compilance will the Corner Recordation Act (70-22-101, et seq., M.C.A.  Signature of Surveyor & Seal  Date: 6/8/2005 Reg. No. 7322-LS
	SKETCH OF CORNER  Employer: Kootenai Surveyors Inc.
record" w was note book No.	Clerk and Recorder, County of Lincoln This "corner  Sec. 4  (as filed for record o: 186337 BOOK: CCR CCER'S PAGE: 10832 Pages: 1  STATE OF MONTANA LINCOLN COUNTY  RECORDED: 07/25/2005 1:20 KOI: CCER'S  CORAL M. CUMMINGS CLERK AND RECORDER  FEE: \$0.00 BY: SEC. 4  Cross Index No. D 10 T. 32N R. 31W P.M., MT  Cross Index No. D 10 T. 32N R. 31W P.M., MT  corner this sheet