INSTRUCTIONS



- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- 3. Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner: 1/4 Corner, Section 31 & 33

T. 32N. R. 33 & 34W. P.M.M. <u>Lincoln</u> County

1981 Record:

Original record not available.

(Ninneman 4661S)

Found std. BLM brass capped monument from which:

Original BT stump, bears N43-1/2°E, 22.0 ft., posted by JWN in 1960 Fir, 10 ins. dia., bears N 51-1/4°E, 9.2 ft., w/ overgrown scribe, posted by ART in 1968 Fir, 8 ins. dia., bears N56-1/2°W, 7.3 ft., scribed "T32NR34W S36 BT", posted by ART

in 1968

2010 Found:

We find a 3-1/4 ins. dia. BLM brass cap, marked as shown below, on 2-1/2 ins. dia. steel

pipe, rising 0.5 ft. from a collar of stone.

From which:

Decaying stump, 12 ins. dia., bears N43°30'E, 22.0 ft., visible blaze "BT"

Douglas Fir, 10 ins. dia., bears N56°30'W, 7.3 ft., w/ overgrown scribing, BT tags Douglas Fir, 14 ins. dia., bears N51°E, 9.2 ft., w/ overgrown scribing, BT tags

Galvanized steel post, bears South, 3.2 ft.

2010 Perpetuation:

We establish no new reference monuments.

We paint red bands on the BTs.

We add more stones around the monument.

T32N R34W R33W 1/4 S36 S31
PROPOSTRAL SURVEY AND MANAGEMENT

SKETCH OF CORNER

CERTIFICATION Keith Brandt certify the information shown herein is true and correct. 15,

Signature Ground Party Chief

MONTA. Ken E Jenkins certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the Corner Recordation Act" (70-22-101, et len M.C.A.)

Signature of Surveyor & Seal

Date: 12/2010 Reg. No. 9330 LS

Employer: Montana Northwest Company

PO Box 8777, Missoula, MT 59807

406-721-4033 Project No. 1617-10

			Sec. 31
Office of Clerk and Recorder, Cour	This "corner 231799 BOOK: CCR CCER'S PAGE: 11768 Pages: 1		
record" was filed for record on STAT	TE OF MONTANA LINCOLN COUNTY		
was noted on the cross-index p	ORDED: 03/30/2011 11:18 KOI: CCSR'S MY D. LAUER CLERK AND RECORDER	•	_
FEE:	80.00 BY: Season Seron Reguly MONTANA HORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA		
	Courte Official		