INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.

2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.

3. Description of monument and accessories set to perpetuate the corner position.

- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner: <u>HES 741 Corner # 7; Secs. 7&12</u> T. <u>32N.</u> R. <u>33&34W.</u> P.M.M. <u>Lincoln</u> County

H.E.S. Record:

Set sandstone and established 2 bearing trees. Raised a mound of earth and stone NE of

corner.

1982 Record: (Hill 5612S)

Found 6 ins. x 6 ins. sandstone, 9 ins. above the ground, mkd "CC7HES741"

on East face, mkd w/ "X" on top. No evidence of bearing trees.

Established new bearing trees:

Fir, 10 ins. dia., bears S04°E, 13.7 ft., mkd "CC7BT"
Cedar, 9 ins. dia., bears S75°W, 19.4 ft., mkd "CC7BT"

Larch, 14 ins. dia., bears S56°W, 7.5 ft., attached location poster

2010 Found:

We find stone monument, 6-1/2 ins. x 8 ins., rising 11 ins. from the ground, w/ visible

scribing on East face.

From which:

Douglas Fir, 11 ins. dia., bears S04°E, 13.7 ft., w/illegible scribing in blaze Cedar, 14 ins. dia., bears S75°W, 19.2 ft., w/ overgrown blaze Larch, 14 ins. dia., bears S56°W, 19.4 ft. (Record 7.5ft.), w/location poster

2010 Perpetuation:

We establish no new reference monuments.

We set a galvanized steel post, South, 1.5 ft. from the monument, w/ LSM, USFS and property boundary decals.

Bearing trees were affixed with BT tags and a painted red band.

CERTIFICATION I, Keith Brandt certify the information shown herein is true and correct. Signature Ground Party Chief WONTAN, I, Ken E Jenkins certify that this Corner Record correctly ORIGINAL STONE represents work performed by me grunder my direction in compliance with the Recordation Act" (70-22-101, et Ken Signature of Surveyor & Seal Date: 12/2010 Reg. No. 9330 LS Employer: Montana Northwest Company PO Box 8777, Missoula, MT 59807 SKETCH OF CORNER 406-721-4033 Project No. 1617-10

			Sec. 12	
Office of Clerk and Recorder,	County of	This "corner		
	231882 BOOK: CCR CCER'S	PAGE: 11825 Pages: 1		
record" was filed for record o	STATE OF MONTANA LINCOLN COUNTY			
was noted on the cross-index	RECORDED: 03/31/2011 10:00 KOI:	CCER'S		
	TAMMY D. LAUER CLERK AND RECORD	ER _ D °- / D		
book No.	FEE: \$0.00 BY:	excee Lenses donte		
	FEE: \$0.00 BY: TO: MONTANA MORTHWEST COMPANY P.O. BO	DX 8777, MISSOULA, MONTANA	<u> </u>	<u> </u>

County Official