

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATIONCorner: E1/16 Corner; Secs. 25&36 T.32N. R. 34W. P.M.M. Lincoln County

Record:

(J.W.N., 534ES)

Corner recordation form (BK. 1, PG. 255). Set a 1-1/2 ins. x 4 ft. bolt, 3 ft. in the ground from which:

A cedar, 8 ins. dia., bears S21°E, 4.4 ft., marked "E 1/16".

A fir, 10 ins. dia., bears N34°W, 20.9 ft., marked "E 1/16".

1983Record:

(Hill, 5612S)

Found monument as noted above, which bears N30°30'E, 13.3 ft from corner position determined by this survey.

At determined corner position, set a 3/4 ins. x 30 ins. aluminum rod, 27 ins. in the ground with aluminum cap from which:

A fir, 8 ins. dia., bears N2°W, 7.1 ft., marked "E 1/16 S25 BT"

A fir, 12 ins. dia., bears S12°E, 32.3 ft., marked "E 1/16 S36 BT"

2010 Found:

We find a 3-1/4 ins. dia. aluminum cap, set firm in a small mound of stone, marked as shown below from which:

A fallen fir, 11 ins. dia., bears N3°W, 7.1 ft., with an overgrown heel blaze.

A fir, 17 ins. dia., bears S18°E, 31.9 ft., with an overgrown heel blaze.

2010 Perpetuation: Establish a new bearing tree as follows:

A fir, 10 ins. dia. bears N36°E, 1.7 ft., scribed "1/16 S25 RM"

Bearing trees affixed with BT tags as needed, LSM signs, snow blazed and red bands. Metal spike driven into BT's side center at point of measurement.

Set a galvanized steel post East, 2.0 ft of the monument with LSM and USFS boundary decals.

**SKETCH OF CORNER****CERTIFICATION**I, Travis R. Williams

certify the information shown herein is true and correct.

Signature Ground Party Chief

I, Ken E Jenkins

certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the Corner Recordation Act" (70-22-101; et seq., M.C.A.)

Signature of Surveyor & Seal

Date: 12/2010 Reg. No. 9330 LSEmployer: Montana Northwest CompanyP.O. Box 8777, Missoula, MT 59807406-721-4033 Project No.1617-10

Sec. 36

Office of Clerk and Recorder, C
record" was filed for record on
was noted on the cross-index pl
book No. _____

231901 BOOK: CCR CC&R'S PAGE: 11844 Pages: 1

STATE OF MONTANA LINCOLN COUNTY

RECORDED: 03/31/2011 10:19 KOI: CC&R'S


TAMMY D. LAUER CLERK AND RECORDER

FEE: \$0.00

BY: Francis Davis

TO: MONTANA NORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA

County Official

Cross Index No. V-24 T. 32N R. 34W PMM

● - Corner this sheet