

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner: S.M.C. on the South boundary T. 32N. R. 34W. P.M.M. Lincoln County
of the SW 1/4 of the NW 1/4 of
the SW 1/4 Section 36

1977 Record:

(Ninneman, 534 ES) Certificate of Survey No. 305. Set a 1/2 ins. x 24 ins. steel rod with cap stamped "J.N. 534 E.S." No bearing trees.

1994 Record:

(Hughes, 7322 LS) Found a 1/2 ins. dia. rebar with a plastic cap marked "J.N. 534ES". No bearing trees found.

Alongside the found rebar, drove a 1/2 ins. dia. x 30 ins. long alum. rod, 26 ins. in the ground, with a 3-1/4 ins. dia. alum. cap.

Established new bearing trees:

A pine, 17 ins. dia., bears S83°E, 50.2 ft., marked "S36 SMC BT"

A fir, 12 ins. dia., bears S44°E, 77.3 ft., marked "S36 SMC BT"

2010 Found:

We find a 1/2 ins. dia. rebar with the remnants of an illegible plastic cap from which:

A Ponderosa pine, 19 ins. dia., bears S80°30'E, 49.2 ft., with an overgrown heel blaze.

A Douglas fir, 14 ins. dia., bears S43°E, 76.6 ft., with an overgrown heel blaze.

NOTE: We do not find any evidence of the 3-1/4 ins. alum. cap.

2010 Perpetuation:

Bearing trees affixed with BT tags, LSM signs, snow blazed and painted red bands. Steel spikes driven into BT's, side center at point of measurement. We set a galvanized steel post East, 2.0 ft. from monument, with LSM and USFS boundary decals.

SKETCH OF CORNER

CERTIFICATION

I, Keith Brandt
 certify the information shown herein is true and correct:

Keith Brandt
 Signature Ground Party Chief

I, Ken E Jenkins
 certify that this Corner Record correctly represents work performed by me, under my direction in compliance with the Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Ken E Jenkins
 Signature of Surveyor & Seal

Date: 12/2010 Reg. No. 9330 LS

Employer: Montana Northwest Company

P.O. Box 8777, Missoula, MT 59807

406-721-4033 Project No. 1617-10

Sec. 36

Office of Clerk and Recorder, County of _____ This "corner

record" was filed for reco: 231905 BOOK: CCR CC&R'S PAGE: 11848 Pages: 1

was noted on the cross-in: STATE OF MONTANA LINCOLN COUNTY


book No. _____ RECORDED: 03/31/2011 10:23 KOI: CC&R'S

TAMMY D. LAUER CLERK AND RECORDER

FEE: \$0.00 BY: Tammy D. Lauer

TO: MONTANA NORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA

County Official



Cross Index No. X-21.22 T. 32N R. 34W PMM

● - Corner this sheet