3. Description of montiment and accessories set to perpendic the chair position.

4. Sketch or corner, show all pertinent data which can best be shown in a sketch example topography ties, position of accessories, etc.

5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

6. Fill in Cross Index & Seciton Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

S28 Corner

P.M.M.

RECORD: No previous record of corner monumentation on file.

FOUND: Nothing to show evidence of a previously monumented corner.


An aluminum pipe 30" long, $2\frac{1}{2}$ " diam., approx. 24" in the ground with a $3\frac{1}{2}$ " SET:

diam., aluminum cap surrounded by a mound of stone and marked as shown.

from which

A spruce, 10" diam., bears N. 77°W., 16.6 feet dist., scribed "\$28 BT".

A aspen, 12" diam., bears S. 01°E., 40.6 feet dist., scribed "S33 BT".



SKETCH OF CO	THOMAS C. HILL 5612 S REGISTERED ORIGINAL SURVENIMENTAL ASPEN ORNER
UKETOINGI CO	NIAEK 1
	ρ

CERTIFICATION
, James W. Reed
certify the information shown herein is true and correct.
James Red
Signature Ground Party Chief
I Thomas C. Hill
certify that this Corner Record correctly represents work performed
by me or under by direction in compliance with the Corner Recordation Act. (20-22-101, et seq., M.D.A.)
Signature of Surveyor & Seal
Date: 6/28/83Reg. No. 5612 S
Employer: U.S.F.S.
<u> </u>

Office of Clerk and Recorder, County of	Lincoln .	This "corner	Sec. 28		
record" was filed for record on the	July 12th	day of 19 <i>83</i>		+-1	
was noted on the cross-index plat and is ass		 , , , , , , , , , , , , , , , , , 		+-+	
book No	rnet BF Siegel by L County Official	Setty L. Conces		┿┽	
Cross I	Index No T 33	alpung.	• corner	r this s	heat

