## **CERTIFIED LAND CORNER RECORDATION**

(REFERENCE FSH 5681.65)


## DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found stone in place and mkd as described (record - sandstone 18" x 10" x 9", 12" in grd. mkd 1/4 on N. face) S 19 BT fir mkd as described (Record 12" fir mkd 1/4 S 19 BT bears N  $76^{\circ}$  E, 17 1ks) S 30 BT 10" fir mkd as described (Record - 10" tamarack mkd 1/4 S 30 BT, bears S  $38^{\circ}$  E, 15 1ks.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 7-9-63

33



Set pipe with brass cap marked as shown:

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

None,

	· · · · · · · · · · · · · · · · · · ·	
Surveyor's Seal	τ .	DIAGRAM OF CORNER:
	certify that the information shown herein is true and correct.	N. T33N R28W
*		<b>1</b> 9
L. L. Levis Britage	Signature of Ground Party Chief	<del></del>
	I,	30
	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.	1/4
	Flamer Berg	= Corner recorded on the sheet
	Signature of Surveyor	
	Registration Number	
Office of Clerk and Recorder, County	of LINCOLN, LIBBY, MONT.	
This "corner record" was filed for re	cord on the 8th. day of OCTOBER 1965, was	noted on the cross-index plat and is
assigned page No30 in	book No. 1 M. M. MANSFIELD,	By: Merde Hyden  y Official Doputy

ģ

. . .

Ċξ

...

. .(

-1

1 - 1 - 1