
CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found original scribed stone (Record - Busalt stone 24" x 12" x 3", 18" in ground, marked w/3 notches on N & S edges). Sec. 18 BT 20" fir as marked (Record - 20" fir marked T33N, R28W, S 18 BT bears N 31°15' E, 65 links). Sec 13 BT 12" fir as described (Record - 12" fir marked T33N, R29W, S 13 BT bears 8°15' W, 90 links). Sec. 19 BT fir as described (Record - 10" fir marked T33N, R28W, S 19 BT bears S 61° E, 16 links). Sec 24 BT 10" fir as described (Record - 10" fir marked T33N, R29W, S 24 BT bears S22° W, 26 links).

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:



Set GI pipe, 1-1/8" diam. 28" long with brass cap marked as shown. Established following BT.

BT 10" fir marked FSBT, bears N 50°15' E, 91 links. BT 12" fir marked FSBT, bears S 81°45; E, 95 links. BT 12" fir marked FSBT, bears S62°10' W, BT 5" tamarack, marked FSBT bears N 49°30' W, 96 links.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

None

This "corner record" was filed for record on the 8th day of

assigned page No...33 in book No...1

		DIAGRAM OF CORNER:
Surveyor's Seal	I,	
The same of the sa	certify that the information shown herein is true and correct.	N. Rg. 29W Rg. 28W
	Signature of Ground Party Chief	Tup 33N 13 18 24 19
	certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.	24/19
	Mornan, Berg	= Corner recorded on the sheet
	Signature of Surveyor	
	Registration Number	
Office of Clerk and Recorder, Cou	inty of LINCOLN, LIBBY, MONTANA	

OC TOBER

Cross Index No... N-25 T. 33

MANSFIELD, By:

County Official

Deputy.

The said of the control of the contr

7 (...)

13 121 TE

ev H