CERTIFIED CORNER REC	ORDATION
Corner E 1/16 S15 T 33 N. R. 31 V	W. P.M.M. Lincoln County
I. <u>Record:</u> None	
II. <u>Found:</u> No monuments found during area search.	
	•
III. <u>Perpetuation:</u> At the corner point, determined by survey, set a 5/8 ins. diam. steel rebar 24 ins. long, 22 ins. in the ground, with a 3 1/4 ins. diam. U.S.D.A Aluminum cap marked as shown below from which:	
A larch, 11 ins. diam., bears S. 2° E., 4.70 ft. dist., scribed E 1/16 S15 BT.	
A fir, 11 ins. diam., bears N. 81° W., 12.50 ft. dist., scribed E 1/16 S10 BT.	
Painted faces and 6 in, wide red bands to all Survey Monument and Bearing Tree signs.	bearing trees and attached Land
Set a steel post on line 4 ft. East of set more Land Survey Monument and Property Boundary	nument with attached stickers.
Magnetic declination: 18* East	
Equipment used: Hand compass and loggers tape	
	T33N R31W E1/16 S10
	$\left(\frac{E1}{16} \frac{S10}{S15}\right)$
	7322 LS 2007
	NTA VA
Kootenai Surveyors Inc., 314 California Av., Libby, MT.	ALVAH F. HUGHES 7322LS
CRUIEN CR PCTC	CERTIFICATION
11" fir	certify the information shown herein is true and correct.
N81 W	Alvah F. Hughes certify that this Corner Record correctly represents work
2/5 2/5	performed by me or under my direction in compliance with the "orner Recordation Act" (70-22-101, et eq., M.C.A.)
11" larch	Signature of Surveyor & Sept Date: 7/24/2007 Reg. No. 7322-LS
SKETCH OF CORNER	Employer: Kootenai Surveyors Inc.
Office of Clerk and Recorder, County of <u>Lincoln</u> . This "corner Sec. 15	
was noted on the cross-index	PAGE: 11109 Pages: 1
book No. TAMMY D. LAUER CLERK AND RECORDER FEE: \$0.00 BY:	/ <u> </u>
TO: KOOTEHAI SURVEYORS INC. P.O.BOX 39:	
Cross Index No. J 16 T. 33N R. 31W P.M., MT * corner this sheet Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors	

· Printed to wind on