CERTIFIED CORNER REC	
I. <u>Record:</u> None	
II. <u>Found:</u> No monuments found during area search.	
III. <u>Perpetuation:</u> At the corner point, determined by some steel rebar 24 ins. long, 22 ins. in the groun U.S.D.A Aluminum cap marked as shown belo	id, with a 3 1/4 ins. diam.
A larch, 8 ins. diam., bears S. 46°30'E., 23.75	5 ft. dist., scribed SE 1/16 S15 BT.
A larch, 12 ins. diam., bears S. 41°W., 25.70 f	ft. dist., scribed SE 1/16 S15 BT.
Painted faces and 6 in. wide red bands to all Survey Monument and Bearing Tree signs.	bearing trees and attached Land
Set a steel post on line 2 ft. East of set mo Land Survey Monument and Property Boundary	
Magnetic declination: 18° East	t.
Equipment used: Hand compass and loggers t	ape ,
	SE 1/16 7322 LS 2007
Kootenai Surveyors Inc., 314 California Av., Libby, MT.  UIEN CR PCTC  S61.W 12.	CERTIFICATION  Levi Powell  Levi Powell  HUGHES  certify the information shown hereint true and correct: LS  Plantature Ground Party Chief?  Alvah F. Hughes  certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Torner Recordation Act" (70-22-101, et seq., M.C.A.)  Signature of Surveyor & Jeal  Date: 7/27/2007 Reg. No. 7322-LS
SKETCH OF CORNER	Employer: Kootenai Surveyors Inc.
Office of Clerk and Recorder, County of Lincoln This	corner Sec. 15
record" was filed for record on  205588 BOOK: CCR CCER'S PAGE  was noted on the cross-in book No.  RECORDED: 08/27/2007 9:32 KOI: CCER  TAMMY D. LAUER CLERK AND RECORDER  FEE: \$0.00 BY:  TO: KOOTEMAL SURVEYORS (Mr. P.O.BOX 393, L.)	Gener douts
Cross Index No. M 16 T. 33N R.	* * * * * * * * * * * * * * * * * * *

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

•